

Dati tecnici

VELOCITA' FISSA	Bar	HP	kW	l/min	m ³ /h	dB(A)	Diam. uscita aria	kg base	kg essicc.
CPC 40 - 60 G									
CPC 40 G/7,5	7,5	40	30	5460	327,6	69	1"1/2	760	945
CPC 40 G/8,5	8,5	40	30	5100	306,0	69	1"1/2	760	945
CPC 40 G/10	10	40	30	4560	273,6	68	1"1/2	760	945
CPC 40 G/13	13	40	30	3840	230,4	68	1"1/2	760	945
CPC 50 G/7,5	7,5	50	37	6720	403,2	71	1"1/2	840	1025
CPC 50 G/8,5	8,5	50	37	6420	385,2	71	1"1/2	840	1025
CPC 50 G/10	10	50	37	5760	345,6	70	1"1/2	840	1025
CPC 50 G/13	13	50	37	4620	277,2	70	1"1/2	840	1025
CPC 60 G/7,5	7,5	60	45	7860	471,6	72	1"1/2	845	1030
CPC 60 G/8,5	8,5	60	45	7620	457,2	72	1"1/2	845	1030
CPC 60 G/10	10	60	45	6960	417,6	71	1"1/2	845	1030
CPC 60 G/13	13	60	45	5940	356,4	71	1"1/2	845	1030
CPD 75 - 100 G									
CPD 75 G/7,5	7,5	75	55	9600	576,0	72	2"	1100	1373
CPD 75 G/8,5	8,5	75	55	9000	540,0	72	2"	1100	1373
CPD 75 G/10	10	75	55	8400	504,0	71	2"	1100	1373
CPD 75 G/13	13	75	55	7200	432,0	71	2"	1100	1373
CPD 100 G/7,5	7,5	100	75	12540	752,4	75	2"	1287	1560
CPD 100 G/8,5	8,5	100	75	11940	716,4	75	2"	1287	1560
CPD 100 G/10	10	100	75	10740	644,4	74	2"	1287	1560
CPD 100 G/13	13	100	75	9420	565,2	74	2"	1287	1560
CPE 100 - 120									
CPE 100/7,5	7,5	100	75	14280	856,8	72	2"	1540	-
CPE 100/8,5	8,5	100	75	13500	810,0	72	2"	1540	-
CPE 100/10	10	100	75	12000	720,0	71	2"	1540	-
CPE 100/13	13	100	75	10140	608,4	71	2"	1540	-
CPE 120/7,5	7,5	125	90	15720	943,2	74	2"	1570	-
CPE 120/8,5	8,5	125	90	15600	936,0	74	2"	1570	-
CPE 120/10	10	125	90	14220	853,2	73	2"	1570	-
CPE 120/13	13	125	90	11640	698,4	73	2"	1570	-