



Serie CPM 3 - 20HP / Dati tecnici

								
Modello	l/min	m3/h	HP	kW	Bar	dB(A)	kg	L x W x H (mm)
su serbatoio 200L + Essiccatore								
CPM 3-8	297	17,8	3	2,2	8	61	187	1429 x 612 x 1300
CPM 3-10	240	14,4	3	2,2	10	61	187	1429 x 612 x 1300
CPM 4-8	443	26,5	4	3	8	61	191	1429 x 612 x 1300
CPM 4-10	320	19,2	4	3	10	61	191	1429 x 612 x 1300
CPM 5,5-8	560	33,6	5,5	4	8	62	193	1429 x 612 x 1300
CPM 5,5-10	470	28,2	5,5	4	10	62	193	1429 x 612 x 1300
CPM 7,5-8	697	41,8	7,5	5,5	8	64	198	1429 x 612 x 1300
CPM 7,5-10	600	36,0	7,5	5,5	10	64	198	1429 x 612 x 1300
CPM 10-8	1008	60,6	10	7,5	8	64	254	1429 x 612 x 1300
CPM 10-10	920	55,2	10	7,5	10	64	254	1429 x 612 x 1300
su serbatoio 270L + Essiccatore								
CPM 3-8	297	17,8	3	2,2	8	61	198	1531 x 612 x 1394
CPM 3-10	240	14,4	3	2,2	10	61	198	1531 x 612 x 1394
CPM 4-8	443	26,5	4	3	8	61	202	1531 x 612 x 1394
CPM 4-10	320	19,2	4	3	10	61	202	1531 x 612 x 1394
CPM 5,5-8	560	33,6	5,5	4	8	62	204	1531 x 612 x 1394
CPM 5,5-10	470	28,2	5,5	4	10	62	204	1531 x 612 x 1394
CPM 7,5-8	697	41,8	7,5	5,5	8	64	209	1531 x 612 x 1394
CPM 7,5-10	600	36,0	7,5	5,5	10	64	209	1531 x 612 x 1394
CPM 10-8	1008	60,4	10	7,5	8	66	236	1533 x 650 x 1352
CPM 10-10	920	55,2	10	7,5	10	66	236	1533 x 650 x 1352
CPM 15-8	1428	33,4	15	11	8	68	250	1533 x 650 x 1352
CPM 15-10	1310	78,6	15	11	10	68	250	1533 x 650 x 1352
CPM 20-8	1750	105	20	15	8	69	258	1533 x 650 x 1352
CPM 20-10	1650	99,0	20	15	10	69	258	1533 x 650 x 1352
su serbatoio 500L + Essiccatore								
CPM 10-8	1008	60,4	10	7,5	8	66	326	1935 x 650 x 1483
CPM 10-10	920	55,2	10	7,5	10	66	326	1935 x 650 x 1483
CPM 10-13	557	33,4	10	7,5	13	66	326	1935 x 650 x 1483
CPM 15-8	1428	33,4	15	11	8	68	340	1935 x 650 x 1483
CPM 15-10	1310	78,6	15	11	10	68	340	1935 x 650 x 1483
CPM 15-13	887	53,2	15	11	13	68	340	1935 x 650 x 1483
CPM 20-8	1750	105	20	15	8	69	348	1935 x 650 x 1483
CPM 20-10	1650	99,0	20	15	10	69	348	1935 x 650 x 1483
CPM 20-13	1190	71,4	20	15	13	69	348	1935 x 650 x 1483